



SUPERIOR **Concert Master™**


All-Welded Lockers **Practical Musical Instrument Storage**

General: Lockers shall be All-Welded "Concert Master Lockers" as manufactured by List Industries Inc. or approved equal. All lockers shall be factory-assembled, of all **MIG** welded construction, in multiple column units to meet job conditions. Assembly of locker bodies by means of bolts, screws, or rivets will not be permitted. Welding of knockdown locker construction is not acceptable. Grind exposed welds and metal edges flush and make safe to touch.

Finishing: All locker parts to be cleaned and coated after fabrication with a seven stage zinc/iron phosphate solution to inhibit corrosion, followed by a coat of high grade enamel electrostatically sprayed and baked at 325 degrees Fahrenheit for a minimum of 30 minutes to provide a tough durable finish. Color to be selected from manufacturer's standard list of colors.

Two-Tone Color Combination: Shall be at no additional cost with the locker body, frame and trim chosen from one color and the doors may be one of any other color chosen from manufacturers standard selection.

Concert Master Doors: Doors to be fabricated from single sheet prime 14 gauge with single bends at top and bottom and double bends at the sides. Doors 20" high and over shall include a 3" wide 18 gauge full height channel door stiffener MIG welded to the hinge side of the door as well as to the top and bottom door return bends and spot welded to the inside of door face to form a rigid torque-free box reinforcement for the door. Doors to be solid (non-perforated) with ventilating perforations in the top and bottom door flanges. Optional music note door perforations are available.



Stainless Steel Recessed Locker Handle: All locker doors shall have a seamless drawn stainless steel recessed handle shaped to receive a padlock or built-in combination lock. The recessed handle shall be deep enough to have the lock be completely flush with the outer door face. The handle pull shall be drawn into the left side of the handle for easy opening of the locker door.

Latch Assembly: Shall be single point rigid non-moving positive latch by means of a heavy 11 gauge (minimum) latch securely welded to the 16 gauge vertical frame member at both the continuous door strike as well as the integral locker side to prevent the latch and frame from twisting. The latch assembly must be made of a single piece of steel and have a padlock loop that inserts through the recess pan. The latch must be able to accept either a padlock or built-in combination lock. A pry resistant lug which inserts into the door shall be an integral part of the 11 gauge latch. Rubber bumpers shall be securely attached to the door strike.

Door Hinges: Hinges for all doors shall not be less than 16 gauge continuous piano type, securely riveted to frame and welded to the door. All doors shall be right hand side hinged.

Frame / Vertical Side Panels: Shall be of integral frame and side wall construction manufactured from solid 16 gauge sheet steel. The one-piece side/frame shall be formed to provide a continuous door strike on the hinge side. An additional continuous vertical door strike shall be achieved at the latch side by MIG welding a 16 gauge full height channel frame member to the integral locker side producing a rigid torque-free welded locker body. The frame shall include a tab which engages a slot in the base locking the side panel and frame into position.

Concert Master™ All-Welded Lockers

Integral Frame Locker Base: 16 gauge formed sheet steel with double return flanges at the front and rear. A full depth horizontal channel shall be MIG welded under the locker bottom front-to-back at the left and right side of each welded locker unit as well as beneath each vertical side panel for maximum rigidity. Optional 4" high integral metal base is available.



Flat Tops: Shall be formed of one piece of 16 gauge cold rolled sheet steel and shall be an integral part MIG welded to each vertical side panel frame member and be continuous to cover the full width of a multiple locker unit.

Hat Shelves, Intermediate Shelves And Bottoms: Shall be 16 gauge sheet steel, have double bends at front and shall be MIG welded to the sides.

Backs: Shall be 18 gauge cold rolled sheet steel, be continuous to cover a multiple column unit and be welded to each vertical side panel.

Lifetime Warranty: Superior All-Welded Lockers by List Industries Inc. are covered against all defects in materials and workmanship excluding finish, damage resulting from deliberate destruction and vandalism under this section for the lifetime of the facility.



Lockers more than 22" Deep

For Concert Master Lockers exceeding 22" deep, two units are field joined front-to-back to accommodate depths up to 44" deep. Tops, shelves and sides include pre-punched flanges for thru-bolting.

Standard Sizes (custom sizes available upon request)

<u>Usage</u>	<u>Width</u>	<u>Depth</u>	<u>Opening Height</u>	<u>Column Height</u>	<u>Tier</u>
Guitars, Baritone Sax	18"	30"	72"	72"	Single Tier
Cellos, Base Drums	24"	30"	84"	84"	Single Tier
Violins, Violas, and Tenor Sax	15"	16"	36"	72"	Double Tier
Tubas, French Horns	30"	40"	36"	72"	Double Tier
Flutes, Oboes	12"	22"	24"	72"	Triple Tier
Baritones, Euphoniums	18"	40"	24"	72"	Triple Tier
Cornets, Trumpets	12"	30"	15"	72"	Four Tier
Alto Sax, Base Clarinets	12"	40"	18"	72"	Four Tier
Trombones, Bassoons	15"	40"	18"	72"	Four Tier
Flutes, Clarinets	12"	30"	12"	72"	Six Tier



www.ListIndustries.com

800-776-1342

401 Jim Moran Blvd., P.O. Box 9601, Deerfield Beach, FL 33442 • Ph 954-429-9115 • Fax 954-428-3843